

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1. (currently amended): An optical sensor for producing an electrical signal in response to electromagnetic radiation, comprising :

a photodetector having an output supplying an electrical signal proportional to the intensity of the electromagnetic radiation striking the photodetector; and

an integrating circuit coupled with the output of the photodetector to accumulate the electrical signal from the photodetector, said integrating circuit comprising :

an operational amplifier having a non-inverting input connected to a non-zero bias voltage, an inverting input coupled to said photodetector, and at least one output;

an integrating voltage storage ~~device~~ device, having a first terminal coupled to the operational amplifier ~~output~~ output, and a second terminal coupled to the operational amplifier inverting input; ~~and~~

an output stage comprising a gate terminal, connected to the operational amplifier output, and an output terminal connected to said first terminal of the integrating voltage storage device, and

switching circuitry for controlling timing of the integrating circuit and switching the integrating circuit between a reset phase and an integration phase,

wherein said switching circuitry includes ~~means for balancing said operational amplifier a~~
first switching device for connecting said operational amplifier output to said operational
amplifier inverting input during said reset phase, and developing a voltage across said integrating
voltage storage device during said reset phase, which voltage is substantially equal to said bias
voltage, said first terminal of the integrating voltage storage device being pulled to a reference
potential during said reset phase means for resetting said integrating voltage storage device
during said reset phase, a voltage equal to said bias voltage being applied across said integrating
voltage storage device, and said first terminal of said integrating voltage storage device being
pulled to a reference potential.

2. (currently amended): The optical sensor according to claim 1, wherein ~~said integrating~~
~~circuit further includes an output stage comprising a gate terminal connected to the operational~~
~~amplifier output and an output terminal connected to said first terminal of the integrating voltage~~
~~storage device, said switching circuitry including: a first switching device for connecting said~~
~~operational amplifier output to said operational amplifier inverting input during said reset phase~~
~~and~~ said first switching device also disconnects ~~for disconnecting~~ said operational amplifier
output from said operational amplifier inverting input during said integration phase; and

wherein said switching circuitry further includes a second switching device for pulling
said output stage output terminal to said reference potential during said reset phase and for

releasing said output stage output terminal from said reference potential during said integration phase.

3. (original): The optical sensor according to claim 2, wherein said output stage is a source-follower output stage.

4. (original): The optical sensor according to claim 1, wherein said integrating voltage storage device is a MOS transistor operating in accumulation mode.

5. (original): The optical sensor according to claim 1, wherein said photodetector is a reverse-biased photodiode.

6. (original): The optical sensor according to claim 1, wherein said operational amplifier is a differential amplifier comprising a differential pair of transistors and having a half-folded cascode stage.

7. (original): The optical sensor according to claim 2, wherein said integrating circuit further comprises a frequency compensation capacitor connected between said output stage gate terminal and said reference potential.

8. (original): The optical sensor according to claim 7, wherein said frequency compensation capacitor is a MOS transistor with common source and drain terminals.

9. (original): The optical sensor according to claim 2, wherein said first and second switching devices are CMOS transistors.

10. (original): The optical sensor according to claim 2, wherein said first and second switching devices are both controlled by a single control signal.

11. (original): The optical sensor according to claim 2, wherein said operational amplifier is a differential amplifier comprising a differential pair of transistors and having a half-folded cascode stage,

said integrating circuit further comprising a first current source coupled to said differential pair of transistors, a second current source coupled to said half-folded cascode stage and a third current source coupled to said output stage.

12. (original): The optical sensor according to claim 11, wherein said second switching device is connected between said output stage output terminal and said third current source, said integrating circuit further comprising a fourth current source connected directly to said output stage output terminal.

13. (currently amended): The optical sensor according to claim 1 for use in an optical sensor array, further comprising a first and second source-follower output stages for providing a minimum and maximum electrical output signals allowing determination of the optical sensor within the array with the least, respectively the greatest intensity. least intensity, and a second source-follower output stage for providing maximum electrical output signal allowing determination of the optical sensor within the array of the greatest intensity.

14. (original): The optical sensor according to claim 13, wherein said first source-follower output stage has a gate terminal connected to said first terminal of the integrating

voltage storage device and a drain terminal connected to a first supply potential, a source terminal of said first source-follower output stage being coupled to a first external current source common to each optical sensor within the array,

and wherein said second source-follower output stage has a gate terminal connected to said operational amplifier output and a drain terminal connected to a second supply potential, a source terminal of said second source-follower output stage being coupled to a second external current source common to each optical sensor within the array.

15. (original): The optical sensor according to claim 1, wherein said non-zero bias voltage is supplied by voltage generating circuitry formed within said integrating circuit.

16. (currently amended): An integrating circuit for use with a photodetector having an output supplying an electrical signal proportional to the intensity of the electromagnetic radiation striking the photodetector, said integrating circuit comprising :

an operational amplifier having a non-inverting input connected to a non-zero bias voltage, an inverting input capable of being coupled to said photodetector, and at least one output;

an integrating voltage storage device having a first terminal coupled to the operational amplifier output and a second terminal coupled to the operational amplifier inverting input;

an output stage comprising a gate terminal connected to the operational amplifier output and an output terminal connected to said first terminal of the integrating voltage storage device;
and

switching circuitry for controlling timing of the integrating circuit and switching the integrating circuit between a reset phase and an integration phase,

wherein said switching circuitry includes ~~means for balancing said operational amplifier~~
first means for connecting said operational amplifier output to said operational amplifier
inverting input during said reset phase, and developing a voltage across said integrating voltage
storage device during said reset phase, which voltage is substantially equal to said bias voltage,
said first terminal of the integrating voltage storage device being pulled to a reference potential
during said reset phase means for resetting said integrating voltage storage device during said
reset phase, a voltage equal to said bias voltage being applied across said integrating voltage
storage device, and said first terminal of said integrating voltage storage device being pulled to a
reference potential.

17. (currently amended): The integrating circuit according to claim 16, wherein said
~~switching circuitry further includes: a~~ said first means for connecting said operational amplifier
output to said operational amplifier inverting input during said reset phase and for disconnecting
also disconnects said operational amplifier output from said operational amplifier inverting input
during said integration phase; and

~~a~~ wherein said switching circuitry further includes second means for pulling said output
stage output terminal to said reference potential during said reset phase and for releasing said
output stage output terminal from said reference potential during said integration phase.

AMENDMENT UNDER 37 C.F.R. § 1.111
U.S. APPLN. NO. 10/073,368

18. (currently amended): The integrating circuit according to claim 16, wherein said output stage is a source-follower output stage.

19. (currently amended): The integrating circuit according to claim 16, wherein said integrating voltage storage device is a MOS transistor operating in accumulation mode.

20. (currently amended): The integrating circuit according to claim 16, wherein said operational amplifier is a differential amplifier comprising a differential pair of transistors and having a half-folded cascode stage.